Technical Data Sheet JIP 127 Food Machinery Lubricant

[Product]





Item No.	JIP 127
Product Name	Food Machinery Lubricant
Volumetric capacity	420 ml
Packing	24 pcs / Box
Country of origin	Japan
NSF	H1, 3H
Approval Number	No.144730

 $6 \text{ pcs} \times 4 \text{ Box} = \text{Total } 24 \text{ pcs}$

COMPONENTS	Gas No.	CHEMICAL FORMULA	WT%
Medium-chain fatty acid triglyceride	65381-09-1	RCOOCH2CH(OCOR)CH2OCOR R=C7H15 C9H19	50-60
Propane	74-98-6	C3H8	5-15
n-butane	106-97-8	C4H10	25-35
Isobutane	75-28-5	C4H10	10 >

[Physical And Chemical Properties]

Appearance	Colorless-Light Yellow Liquid	Specific Gravity	0.948
Odour	Tasteless odorless	Solubillity In Water	Insolble
РН	5.8 (1%aq)	Expiration date	4 years after the date
Flash Point	242 °C		of manufacture

[Date of manufacture]

The Expiration date is Jan. 01, 2024





[Features]

• This Lubricant, Itself is eatable. Produced on Food oil Line.

• Liquid lubricating oil, with vegetal fatty acid of a high degree of purity as major ingredient.

• The properties of liquidity, permeability, digestible and absorbable, witch cannot be found in other general vegetable oil.

• Super oxidation stability (preservation), able to keep long lubricating effect.

• Biodegradable and non-toxic. The composition – Triglyceride is used for processing food and medicine.

[Applications]

- Used as lubricating agent for food processing machines
- Used as mold releasing agent for food containers
- As lubricant for food-cutter, meanwhile, preventing food adhere etc.



(Prevention)

• Keep away from the ignition source of hot, the spark, the naked light, and the high temperature.

- Do not spray the specified or more.
- Should not used in the room using fire.

